

CLAIM AMENDMENTS

Claim 1 (Previously Presented)

A toner for developing an electrostatic image comprising a resin and a colorant in which an arithmetic average of shape coefficient SF-1 of the toner particles calculated by Equation 1 is from 125 to 170 and a ratio of that to an arithmetic average of shape coefficient SF-2 of the toner particles calculated by Equation 2, SF-1/SF-2, is from 1.10 to 1.52 and the ratio of the toner particles having a circle corresponding diameter measured by a flow particle image analyzer of from not less than 0.60 to less than 1.00 μm is not more than 5.0% in number

Formula (1)

$$SF-1 = \frac{(\text{Maximum diameter of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100\pi}{4}$$

Formula (2)

$$SF-2 = \frac{(\text{Circumference of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100}{4\pi}$$

Claim 2 (Withdrawn)

A production method of a toner comprising a resin and a colorant wherein the method comprises a step of fusing resin particles in an aqueous medium, in which an arithmetic average of the shape coefficient SF-1 of the toner particles calculated by Equation 1 is from 125 to 170 and a ratio of that to an arithmetic average of the shape coefficient SF-2 of the toner particles calculated by Equation 2, SF-1/SF-2, is from 1.10 to 1.52 and the ratio of the toner particles having a circle corresponding diameter measured by a flow particle image analyzer of from not less than 0.60 to less than 1.00 μm is not more than 5.0% in number

Formula (1)

$$SF-1 = \frac{(\text{Maximum diameter of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100\pi}{4}$$

Formula (2)

$$SF-2 = \frac{(\text{Circumference of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100}{4\pi}$$

Claim 3 (Withdrawn)

An image forming method comprising developing an electrostatic latent image formed on a photoreceptor by facing the static latent image to a layer of a single-component developer formed on a developer conveying member so as to touch with together, in which the single-component developer comprises a toner comprising a resin and a colorant and an external additive, an arithmetic average of the shape coefficient SF-1 of the toner particles calculated by Equation 1 is from 125 to 170 and a ratio of that to an arithmetic average of the shape coefficient SF-2 of the toner particles calculated by Equation 2, SF-1/SF-2, is from 1.10 to 1.52 and the ratio of the toner particles having a circle corresponding diameter measured by a flow particle image analyzer of from not less than 0.60 to less than 1.00 μm is not more than 5.0% in number

Formula (1)

$$SF-1 = \frac{(\text{Maximum diameter of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100\pi}{4}$$

Formula (2)

$$SF-2 = \frac{(\text{Circumference of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100}{4\pi}$$

Claim 4 (Withdrawn)

An image forming method comprising a developing step of developing a static latent image formed on a photoreceptor by an ~~static image developer comprising a toner comprising a resin and~~ a colorant and an external additive, wherein the step of transferring the toner to an image receiving material, the step of removing the toner remained on the photoreceptor by a cleaning member and the step of recycling the toner removed from the photoreceptor to the developing step, in which an arithmetic average of the shape coefficient SF-1 of the toner particles calculated by Equation 1 is from 125 to 170 and a ratio of that to an arithmetic average of the shape coefficient SF-2 of the toner particles calculated by Equation 2, SF-1/SF-2, is from 1.10 to 1.52 and the ratio of the toner particles having a circle corresponding diameter measured by a flow particle image analyzer of from not less than 0.60 to less than 1.00 μm is not more than 5.0% in number

Formula (1)

$$SF-1 = \frac{(\text{Maximum diameter of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100\pi}{4}$$

Formula (2)

$$SF-2 = \frac{(\text{Circumference of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100}{4\pi}$$

Claim 5 (Withdrawn)

An image forming method comprising a step of developing an electrostatic image formed on a photoreceptor by double-component developer comprising a carrier and a toner comprising a resin and a colorant, in which an arithmetic average of the shape coefficient SF-1 of the toner particles calculated by Equation 1 is from 125 to 170 and a ratio of that to an arithmetic average of the shape coefficient SF-2 of the toner particles calculated by Equation 2, SF-1/SF-2, is from 1.10 to 1.52 and the ratio of the toner particles having a circle corresponding diameter measured by a flow particle image analyzer of from not less than 0.60 to less than 1.00 μm is not more than 5.0% in number

Formula (1)

$$SF-1 = \frac{(\text{Maximum diameter of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100\pi}{4}$$

Formula (2)

$$SF-2 = \frac{(\text{Circumference of toner particle})^2}{(\text{Projection area of toner})} \times \frac{100}{4\pi}$$

~~Claim 6 (Previously Presented)~~

The toner of claim 1 wherein the content of the particles having the ratio SF-1/SF-2 of from 1.20 to 1.35, is not less than 60% in number.

Claim 7 (Previously Presented)

The toner of claim 1 wherein the value of SF-1 is from 130 to 165.

Claim 8 (Previously Presented)

The toner of claim 7 wherein the value of SF-1 is from 135 to 160.

Claim 9 (Previously Presented)

The toner of Claim 7, comprising a compound represented by following formula:



wherein n is an integer of 1 to 4; R_1 and R_2 each represent a hydrocarbon group which may have a substituent.

Claim 10 (New)

The toner of claim 1, wherein ratio of toner particles having the ratio SF-1/SF-2 of from 1.1 to 1.52 is not less than 95% in number.

Claim 11 (New)

The toner of claim 1, wherein ratio of toner particles having the ratio SF-1/SF-2 of from 1.20 to 1.35 is not less than 60% in number.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☒ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.